

IN THE CLAIMS

Please amend the claims as follows:

Claims 1 - 13 (Canceled).

Claim 14 (Currently Amended): ~~The data relay system according to claim 13 further comprising:~~ A data relay system having a logical tunnel established within a specified public network interposed between a specified backbone network and host devices, which relays data between the backbone network and the host devices through the logical tunnel, the system comprising:

a first data relaying apparatus, disposed within the specified public network, for relaying data between the backbone network and the host devices through the logical tunnel established within the public network, the data relaying apparatus comprising

a first type determination unit configured to monitor contents of the data laded from the host device and determine a type of the data;

a first relay unit configured to relay data through the tunnel when the type of the data is targeted for a single traffic;

a first control processing unit configured to perform control processing on the data without being routed through the tunnel when the data is a predetermined control packet, wherein

when the data loaded from said host device is the predetermined control packet, the first data relaying apparatus performs control processing so as to relay the data without routing through the logical tunnel, and

a first ~~second~~ data relay apparatus, disposed within the a specified public network interposed between a specified backbone network and host devices, which relays for relaying

data between the backbone network and the said host devices ~~through a logical tunnel~~
~~established within the public network~~, said ~~first~~ second data relay apparatus comprising[[:]]

a second type determination unit configured to monitor ~~that monitors~~ contents
of the data loaded from the backbone network and determine ~~determines~~ a type of the
data;

a second relay unit configured to relay ~~that relays~~ data through the tunnel
when the type of the data is targeted for a single traffic; and

a storage control unit configured to store ~~that stores~~ the data when the type of
the data is targeted for broadcast to a particular group; and

a ~~second~~ third data relay apparatus, disposed within the a specified public network
~~interposed between a specified backbone network and host devices, for relaying which relays~~
data between the backbone network and said host devices ~~through a logical tunnel established~~
~~within the public network~~, said second data relay apparatus comprising[[:]]

a ~~first~~ third type determination unit configured to monitor ~~that monitors~~
contents of the data loaded from said host device and determines a type of the data;

a ~~first~~ third relay unit configured to relay ~~that relays~~ data through the tunnel
when the type of the data is targeted for a single traffic; and

a second control processing unit configured to ~~that performs~~ control
processing on the data without being routed through the tunnel when the data is a
predetermined control packet,

wherein said second control processing unit of said ~~second~~ third data relay apparatus
performs control processing so as to relay the data, as a target to be controlled stored by said
storage control unit of said first data relay apparatus, to said host device that has issued a
specified reception request.

Application No. 10/015,658
Reply to Office Action of August 19, 2005

Claim 15 (Canceled).